

Picture shows special equipment

## HFFS Pouch-Packaging Machine in Hygienic-Design FMH 80


Intermittent working HFFS rotary machine with eight stations in hygienic design to produce, fill and seal flat or stand-up pouches from roll stock - also with reclosure systems.


Application range: Food, Pet Food, Beverages, Pharmaceuticals, Nonfood, Household, Personal Care.

- Complies with the highest hygiene requirements of the food industry
- Very easy to clean thanks to the open machine construction
- Consequent reduction of corners, edges and plain surfaces to prevent dirt deposits
- Ideal for liquids and powder products
- Central operation and visualization via touch control panel
- Direct driven unwinding and brake function
- Dosing equipment: Auger doser, slide doser, rotary and valve pumpdoser, flow-meter; synchronization with linear and multihead scales



Uniquely customized. Uniquely economical.





Technical details FMH 80			
Specification	FMH 80 135 SIMPLEX	FMH 80 225 DUPLEX	FMH 80 935 SIMPLEX / DUPLEX
Pouch size [mm]	Width 50 - 280 Length 80 - 350	Width 2 x 50 - 130 Length 80 - 250	Width 50 - 280 (simplex) Width 50 - 130 (duplex) Length 80 - 250 / 350
Machine output [Pouches/min]	up to 100* * depend	up to 200* ding on filling characteristics and po	up to 200* ouch size
Packing material	sealable laminated film		
Construction	standard to proceed dry products or wash down construction		
Safety equipment	acc. to the international safety regulations e.g. CE, UL, CSA, OSHA		
Noice level [dBA]	≤ <b>80</b> ¹)		
Electricity power [kVA]	ca. 30 <sup>1)</sup>		
Electricity supply	3 x 400/230V + N + PE, 50/60 HZ		
Voltage [V]	400 / 230 / 24		
Air consumption	ca. 550 Nl/min, 6 bar 1)	ca. 650 Nl/min, 6 bar 1)	ca. 650 Nl/min, 6 bar 1)
Machine dimensions L x W x H [mm]	ca. 6.300 x 1.750 x 2.400 <sup>1)</sup>		
1) Depending on configuration — Technical modifications reserved.			

Standard equipment	Optional equipment	
Hygienic design (e.g. closed cavities)	Date code systems	
Wash down construction	Stand-up pouch device	
Machine frame in stainless steel	Reclosure systems	
Direct driven unwinding and brake funktion	Recipe management	
Servo driven sealing device	Nitrogen gassing	
Central operation and convenient process control	Ultrasonic sealing	
PLC Siemens or Allen Bradley (Rockwell)	Servo driven block-adjustment of sealing frames, camera controlled	
Teleservice	Mirror-inverted execution	
	(further details on request)	

